



US009636951B2

(12) **United States Patent**  
**Colombo et al.**

(10) **Patent No.:** **US 9,636,951 B2**

(45) **Date of Patent:** **\*May 2, 2017**

(54) **TIRE WITH TREAD HAVING CONTINUOUS RIB**

(71) Applicants: **Gianfranco Colombo**, Concorezzo (IT); **Giancarlo Cucco**, Villa Cortese (IT); **Vito Bello**, Monza (IT)

(72) Inventors: **Gianfranco Colombo**, Concorezzo (IT); **Giancarlo Cucco**, Villa Cortese (IT); **Vito Bello**, Monza (IT)

(73) Assignee: **PIRELLI PNEUMATICI S.P.A.**, Milan (IT)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 702 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/029,320**

(22) Filed: **Sep. 17, 2013**

(65) **Prior Publication Data**

US 2014/0014247 A1 Jan. 16, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 12/318,004, filed on Dec. 19, 2008, now Pat. No. 8,701,725, which is a (Continued)

(30) **Foreign Application Priority Data**

Mar. 30, 2001 (EP) ..... 01201232

(51) **Int. Cl.**

**B60C 11/03** (2006.01)

**B60C 11/11** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B60C 11/03** (2013.01); **B60C 11/0302** (2013.04); **B60C 11/0306** (2013.04);

(Continued)

(58) **Field of Classification Search**

CPC ..... B60C 11/0302; B60C 2011/0383; B60C 11/0306; B60C 2011/0388;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D71,229 S 10/1926 Vance  
2,100,084 A 11/1937 McNeill

(Continued)

FOREIGN PATENT DOCUMENTS

DM 048371 9/1999  
EP 0 565 270 A1 10/1993

(Continued)

OTHER PUBLICATIONS

Machine translation for JPH07-290909 A.

*Primary Examiner* — Steven D Maki

(74) *Attorney, Agent, or Firm* — Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.

(57) **ABSTRACT**

A tyre for a motor vehicle includes a tread and two shoulders. The tread includes a circumferential row of blocks between first and second circumferential grooves. Each of the blocks is delimited by a section of the first circumferential groove and by first and second transverse grooves that terminate at a common vertex spaced from the second circumferential groove. The common vertex is separated from the second circumferential groove by a continuous circumferential tread rib. The second transverse groove delimits one of the blocks and is separated from the first transverse groove that delimits a circumferentially adjacent block by a solid tread portion. The solid tread portion extends from the first circumferential groove to the continuous circumferential tread rib. The common vertex of each block is located at a position axially intermediate the first

(Continued)

